

Polar[®]

Premium White

The high opacity of Polar[®] Premium White provides an excellent printing surface and offers a consistent white point. This phthalate-free film also offers excellent indoor and outdoor durability. Polar[®] Premium White has a gloss or matte white finish with permanent adhesive which maximises the adhesive performance on a wide variety of substrates.

- IDEAL FOR INDOOR & OUTDOOR GENERAL GENERAL SIGNAGE & DISPLAY
- SUITABLE FOR MANY APPLICATIONS
- CAN BE USED FOR VEHICLE LIVERY- FLAT OR SLIGHTLY CURVED SURFACES

Product Code:

PDP (Polar Premium White Gloss P)

PDA (Polar Premium Matte P)

80
micron

White
Polymeric
PVC

■
Matte
or Gloss



(Eco)Solvent
Latex
UV



Clear
Permanent
Acrylic Adhesive



Widths up to 1524mm



7 YEARS DURABILITY
INTERIOR & EXTERIOR

(with matched overlamine)

EXCELLENT PRINTING SURFACE



APPLICATIONS

GENERAL SIGNAGE

WINDOW GRAPHICS

EXHIBITION GRAPHICS

POS DISPLAY

DRYTAC[®]

ADHESIVE SCIENCE

www.drytac.com

Polar[®]

Premium White

Polar[®] Premium White is an 80µ (3.2 mil) premium, phthalate-free printable polymeric self-adhesive PVC film with a high quality, clear solvent acrylic adhesive. The high opacity of Polar[®] Premium White provides a consistent printing surface and offers a superb white point. Polar[®] Premium White P is available with as gloss or matte white polymeric PVC film finish with a clear permanent adhesive.

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE USED FOR VEHICLE LIVERY- FLAT OR SLIGHTLY CURVED SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Gloss or Matte White Polymeric PVC
Adhesive	Clear Permanent Solvent Acrylic Adhesive
Release Liner	140 gsm 2 Side PE Coated, 1 Side Siliconised White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ) 4.2 mil (105µ)
Adhesive Layer	1 mil (25µ) (105µ)
Outdoor Durability	7 Years
Fire Rating (EN 13501-1)	Class C-s1, d0
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar[®] Premium, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar[®] Premium are Drytac's Weathershield™ laminating films.

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com