

Trimount™ is a 2.6 mil (65µ) pH-neutral white mounting tissue, coated on both sides with a heat-activated solvent acrylic adhesive that is tack-free at normal ambient temperature and does not require a release liner.

- FOR USE IN ALL TYPES OF DRY MOUNTING PRESSES
- RECOMMENDED FOR BONDING RESIN-COATED PHOTOGRAPHIC PAPER AND PRINTED MATERIALS TO SMOOTH SURFACES
- THIS ADHESIVE HAS EXCELLENT LONG-TERM STABILITY AND WILL NOT NEGATIVELY IMPACT ANY COMPATIBLE SUBSTRATE OR MEDIA IN LONG-TERM APPLICATIONS UNDER NORMAL STORAGE CONDITIONS.

PRODUCT STRUCTURE

Adhesive	Solvent Acrylic (Heat Activated)
Film	Off White Kraft Paper
Adhesive	Solvent Acrylic (Heat Activated)

PRODUCT CHARACTERISTIC

Paper Weight	50 gsm	3.6 mil (89µ)
Adhesive Layer	0.5 mil (12µ) on each side	
Film/Adhesive Ratio	0.5:2.6:0.5	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Not Recommended	Not Recommended
Press 194°F to 210°F (90°C to 99°C)	60 - 90 seconds

DRYTAC
ADHESIVE SCIENCE

For more information,
performance and warranty
guidelines please contact your
local Drytac office.

© 2023 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401 B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013