

UltraTac™ is a 0.5 mil (12µ) clear PET high tack, high bond strength film, coated on both sides with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner.

PRODUCT STRUCTURE

Adhesive	Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	0.5 mil (12µ)
Adhesive Layer	1.1 mil (28µ) on each side
Film/Adhesive Ratio	1.1:0.5:1.1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

- ULTRATAC™ IS A HIGH GRADE VERSION OF MEDIATAC™, SUITABLE FOR ALL THE SAME APPLICATIONS AND DESIGNED FOR MOUNTING GRAPHICS ONTO MORE DIFFICULT SUBSTRATES, SUCH AS FOREX™, MDF, GATORBOARD™, ULTRABOARD™, FOAMEX™, OR SINTRA™.

For more information,
performance and warranty guide
lines please contact your local
Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.