

# ViziCling™

## White & Clear

ViziCling™ is an 7 mil (175µ) adhesive-free static cling PVC film that is offered in gloss clear and white opaque versions. It can be easily applied to and removed from glass and other highly polished, flat surfaces. The nonprinted side of the film adheres securely to windows - no adhesive required! Highly durable and flexible, ViziCling™ provides exceptional clarity and excellent chemical resistance.

- IDEAL FOR SHORT-TERM INDOOR WINDOW APPLICATIONS, INCLUDING WINDOW GRAPHICS, DECALS AND LABELS
- SUITABLE FOR RETAIL AND RESTAURANT SPACES

**7**  
mil

White or Clear  
Static Cling  
PVC



Gloss



(Eco) Solvent  
UV  
Latex



No  
Adhesive



Widths up to 54 in



2 YEARS DURABILITY  
INTERIOR (of glass)

## CLING TO SIMPLE WINDOW GRAPHICS



### APPLICATIONS

Smooth Flat Surfaces  
Window Graphics  
Decals



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ViziCling™

## White & Clear

ViziCling™ is an 7 mil (175µ) flexible, white opaque or clear static cling PVC film with a PE coated Kraft release liner for exceptional clarity. No adhesive is required. It can be easily applied to and quickly removed from most smooth, flat surfaces. The film is very durable and offers excellent chemical resistance and adhesion. The non-printed side of the vinyl adheres securely to glass and other highly polished surfaces.

- IDEAL FOR APPLICATIONS ON GLASS AND OTHER SMOOTH, FLAT SURFACES.
- CAN BE USED FOR WINDOW GRAPHICS, DECALS AND LABELS

### INSTALLATION RECOMMENDATION

Wet installation is recommended for ViziCling™. The surface must be clean and smooth and free of defects before application. ViziCling™ may be used for temporary applications to exterior glass, up to 3 months. Temperature, wind and rain also limit the bond of static cling vinyl to exterior windows.

### PRINTING RECOMMENDATIONS

- Handle material with care prior to printing; use gloves to avoid fingerprints.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	White Opaque Flexible PVC or Gloss Clear Flexible PVC
<b>Adhesive</b>	None
<b>Release Liner</b>	PE Coated Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	7 mil (175µ)   15 mil (375µ)
<b>Release Liner</b>	8 mil (200µ)
<b>UV Protection Factor</b>	Not Applicable
<b>Outdoor Durability</b>	2 Years (interior of glass)
<b>Application Temperature</b>	>40°F (4°C)
<b>Service Temperature Range</b>	-10°F to 150°F (-23°C to 65°C)
<b>Film Melting Point</b>	(320°F (160°C))
<b>Shelf Life</b>	6 months
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**Important Note:** ViziCling™ Clear is a highly plasticized clear static cling that may develop a surface haze. Typically, the haze will dissipate after the decal is applied. Although clear static is exceptionally transparent, flow lines may be visible to varying degrees. Excessive heat over 25°C and humidity greater than 50% increases the rate of plasticizer migration. This could affect printability and ink adhesion.

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013