

Paper Fleece

Smooth

Paper Fleece Smooth is a PVC-free, non-woven wallcovering film designed for long-term use, boasting excellent dimensional stability. Its smooth satin finish makes it perfect for creating vibrant custom wallcoverings in various settings like homes, retail stores, hotels, and offices. With a repositionable permanent adhesive and an air-egress release liner, applying it is a breeze, ensuring a bubble-free finish and allowing for easy repositioning. Plus, its photorealistic print quality produces sharp, detailed graphics with quick drying times, ideal for creating stunning, vivid designs.

- PVC-FREE WALLCOVERINGS
- REPOSITIONABLE PRESSURE SENSITIVE FOR EASY PEEL AND STICK WALL GRAPHICS AND WALLCOVERINGS
- PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS

PRODUCT CODE: CCIP

180 Non-Woven
gsm Paper Fleece

■
Satin



(Eco) Solvent
Latex
UV



Clear Repositionable
Permanent Acrylic
Adhesive



Widths up to 54 in

YEARS DURABILITY
5

INTERIOR

UNIQUE & VIBRANT WALLCOVERINGS



APPLICATIONS

HOTEL DÉCOR

RETAIL STORES

INTERIOR DÉCOR

OFFICES



DRYTAC®
ZERO

www.drytac.com

Paper Fleece

Smooth

Paper Fleece Smooth is a user-friendly 180gsm non-woven paper fleece wallcovering film featuring a clear repositionable permanent acrylic adhesive. Protected by a 140 gsm clay-coated release liner equipped with bubble-free technology, it ensures hassle-free application and repositioning. It is also an eco-friendly solution, meeting the rising demand for sustainable products among consumers.

- IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE
- WITH ITS SUPERIOR DIMENSIONAL STABILITY, THIS PRODUCT GUARANTEES LONG-LASTING DURABILITY AND RETAINS ITS SHAPE OVER TIME, MAKING IT IDEAL FOR A MULTITUDE OF APPLICATIONS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film	Satin White Non-Woven Paper Fleece
Adhesive	Clear Repositionable Permanent (Pressure Sensitive)
Release Liner	140 gsm Clay Coated Release Paper with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	180 gsm
Adhesive Layer	1.2 mil (30µ)
Outdoor Durability	Not Applicable
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Fire Rating	Class B-s1,d0 (EN 13501-1 : 2018) Class B or 2 (ASTM E-84) PASS (CAN/ULC-S102)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

INSTALLATION RECOMMENDATION
Please see Wall Graphic Installation & Removal Instructions for further details. The surface must be clean and smooth and free of defects before application.



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013