

# PaperTac™

## White Matte

PaperTac™ White Matte is a premium coated paper with clear permanent adhesive, ideal for retail promotion, advertising, events, and more. Designed for exceptional print quality across a range of printers—including aqueous, latex/resin, and UV—this versatile media delivers stunning photorealistic prints, making it perfect for short-term applications and eco-conscious projects.

Engineered for durability, PaperTac™ White Matte features water-repellent and scratch-resistant properties, ensuring long-lasting indoor performance. Its clear permanent adhesive allows for easy mounting to rigid card substrates, eliminating the need for a flatbed printer when creating printed boards.

For brands and print professionals seeking a sustainable solution without compromising on quality, PaperTac™ White Matte delivers the perfect balance of performance and eco-responsibility.

**140**  
gsm Coated  
Paper



Aqueous  
Latex/Resin  
UV



Clear Permanent  
Acrylic  
Adhesive

 Widths up to 1250mm

 3 YEARS DURABILITY INTERIOR

## ADHESIVE PAPER FOR VIBRANT PRINTS



### APPLICATIONS

- RETAIL PROMOTIONS
- EVENT GRAPHICS
- MOUNT TO BOARDS



[www.drytac.com](http://www.drytac.com)

# PaperTac™

## White Matte

PaperTac™ is a high-quality 140gsm matte-coated paper designed for wide color gamut aqueous printers, and is also suitable for use on latex/resin, and UV printers. This versatile media is ideal for photorealistic prints, short-term advertising, and other eco-friendly applications. Its water-repellent and scratch-resistant properties ensure durability for indoor use.

Featuring a clear permanent adhesive, PaperTac™ can be easily mounted to rigid card substrates, allowing users to create printed boards without the need for a flatbed printer. It is backed by a 100gsm double-sided PE Kraft siliconized release liner, ensuring smooth handling and application.

PaperTac™ is an eco-conscious solution, catering to the growing demand for sustainable print media without compromising on print quality and performance.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte Coated Paper
<b>Adhesive</b>	Clear Permanent Water Based (Acrylic)
<b>Release Liner</b>	100 gsm 2 Sided PE Siliconised Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	140 gsm
<b>Adhesive Layer</b>	0.6 mil (14µ)
<b>Outdoor Durability</b>	Not Applicable
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	41°F to 104°F (5°C to 40°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013